



Request for Proposal Six Wheel Municipal Plow Truck

General:

The Town of Enfield, NH (hereafter referred to as the “TOWN”) invites qualified firms to submit proposals for the replacement of the six wheel municipal plow truck (hereafter referred to as the “CONTRACTOR”). Details of the project will be covered in the scope of work section of this document.

Instructions:

Proposals must be submitted in a sealed envelope or electronically via the email to the contact below no later than 12:00 P.M. EST on Friday, April 14, 2023. Envelope must be clearly marked “Plow Truck” and will be opened publicly at that time. **Proposals delivered after the time listed above will not be accepted.**

Submit proposals to:

James L. Taylor
Public Works Director
PO Box 373
74 Lockehaven Rd.
Enfield NH 03748.
(603) 632-4605

Bids can also be submitted electronically to jtaylor@enfield.nh.us

Questions can be submitted to the contact above.

Proposal specifications are available on the Town’s web site at:

<https://www.enfield.nh.us/new-enfield-projects/pages/requests-proposals-rfps-qualifications-rfqs>

Scope of Work:

The Town of Enfield is seeking proposals for the replacement of a six-wheel municipal plow truck outfitted with a front plow, wing plow, municipal side dump sand spreader body with the following specifications:

Truck Cab and Chassis:

Base Chassis SFA with 171.00 Wheelbase, 96.00 CA, and 63.00 Axle to Frame.

AXLE CONFIGURATION 4x2

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL

BUMPER, FRONT Swept Back, Steel, Heavy Duty

FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline

FRAME EXTENSION, FRONT Integral; 20" In Front of Grille

WHEELBASE RANGE 146" (370cm) Through and Including 195" (495cm)

AXLE, FRONT NON-DRIVING Wide Track, I-Beam Type, 20,000-lb Capacity

SUSPENSION, FRONT, SPRING Multileaf, Shackle Type, 20,000-lb Capacity, Less Shock Absorbers

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

- BRAKE LINES Color and Size Coded Nylon
- DRAIN VALVE Twist-Type
- GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
- PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel
- PARKING BRAKE VALVE For Truck
- QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4
- SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

DRAIN VALVE {Berg} with Pull Chain, for Air Tank

AIR BRAKE ABS 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

AIR DRYER with Heater

BRAKE CHAMBERS, REAR AXLE 30/30 SqIn Spring Brake

BRAKE CHAMBERS, FRONT AXLE 24 SqIn

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

SLACK ADJUSTERS, FRONT Automatic

SLACK ADJUSTERS, REAR Automatic

AIR COMPRESSOR 18.7 CFM

AIR TANK Painted Aluminum, with Straight Thread O-Ring Ports

AIR DRYER LOCATION Mounted Outside Right Rail, Back of Cab

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

AIR TANK LOCATION (2) : One Mounted Under Each Rail, Front of Rear Suspension,

Parallel to Rail

BRAKES, REAR Air S-Cam Type, Cast Spider, Cast Shoe, Double Anchor Pin, Includes Greaseable and Zinc Coated Anchor Pins, Size 16.5" X 7", 38,000- lb Capacity per Axle

BRAKES, FRONT Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity

STEERING COLUMN Tilting and Telescoping

STEERING WHEEL 4-Spoke; 18" Dia., Black

STEERING GEAR (2) Dual Power

DRIVELINE SYSTEM SPL170, for 4x2/6x2

AFTERTREATMENT COVER Polished Aluminum

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

ENGINE COMPRESSION BRAKE {Jacobs} with Selector Switch and On/Off Switch

TAIL PIPE (1) Turnback Type, Bright

EXHAUST HEIGHT 10'

MUFFLER/TAIL PIPE GUARD (1) Aluminum

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

- DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
- HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
- HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- STARTER SWITCH Electric, Key Operated
- STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
- TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
- WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
- WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- WIRING, CHASSIS Color Coded and Continuously Numbered
- HORN, ELECTRIC (2) Disc Style
- ALTERNATOR Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount
- BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/Backup/ Accessory Power/Ground and Sealed Connector for Stop/Turn
- ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket
- BATTERY SYSTEM Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud

- TAILLIGHT WIRING MODIFIED Includes: Wiring for Standard Lt & Rt Tail Lights; Separate 8.0' of Extra Cable Wiring for Lt & Rt Body Mounted Tail Lights
- 2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
- SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars
- ANTENNA for Increased Roof Clearance Applications
- RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input
- AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications
- TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch
- BATTERY CABLES with 36" of Extra Length Coiled and Strapped Near Battery Box
- BATTERY BOX Steel, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Cab
- WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time
- CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Flush Mounted on Cab or Sunshade
- TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back- up Lights
- HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
- INDICATOR, LOW COOLANT LEVEL with Audible Alarm
- ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened
- STARTING MOTOR 12-Volt, with Soft-Start
- CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
- TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
- HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord
- HEADLIGHTS Halogen

FENDER EXTENSIONS Rubber

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

HOOD, HATCH (01) for Servicing

GRILLE Stationary, Chrome

INSULATION, SPLASH PANELS for Sound Abatement

BUG SCREEN Mounted Behind Grille

FRONT END Tilting, Fiberglass, with Three Piece Construction

CHASSIS COATING Corrosion Resistant E-Coat Primer Coating for Single Frame Rails

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

- PAINT SCHEMATIC ID LETTERS "WK"
- PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
- COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan
- PROMOTIONAL PACKAGE Government Silver Package

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted

ENGINE, DIESEL 330HP @ 2200 RPM, 1000 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 330 Peak HP

FAN DRIVE Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

- FAN Nylon

RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler

Includes

- DEAERATION SYSTEM with Surge Tank
- HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps
- RADIATOR HOSES Premium, Rubber

AIR CLEANER Dual Element, with Integral Snow Valve and In-Cab Control

EMISSION, CALENDAR YEAR EPA, OBD and GHG Certified for Calendar Year 2023

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

ACCESSORY WIRING, SPECIAL for Road Speed Wire Coiled Under Instrument Panel for Customer Use

ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control

HOSE CLAMPS, RADIATOR HOSES Coil Spring/"T"-Bolt Constant Torque Type, for Radiator Hoses over 1" I.D.

BLOCK HEATER, ENGINE 120V/1000W, with "Y" Cord for Dealer Installed 120V/ 300W Oil Pan Heater

Includes

- BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations

CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty

TRANSMISSION, AUTOMATIC {Allison 3500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway

OIL COOLER, TRANSMISSION Water to Oil Type

SHIFT CONTROL PARAMETERS 3000 or 4000 Series Transmissions, 3 Speed S1 Secondary Shift Schedule for 5 or 6 Speed

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission

AXLE, REAR, SINGLE Reduction, 30,000-lb Capacity, Driver Control Locking Differential, W Wheel Ends. Gear Ratio: 6.14

SUSPENSION, REAR, SINGLE {Chalmers style 1030 Series} 30,000-lb Capacity, Rubber Springs, 9.37" Ride Height, 7" High Spring X-Low Mount, with 21" Lower Torque Rods, and Shock Absorbers Mounted Forward

DEF TANK 9.5 US Gal (36L) Capacity, Frame Mounted Outside Left Rail, Under Cab

FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor, Mounted on Engine

FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 80 US Gal (303L), Mounted Left Side, Under Cab

CAB Conventional, Day Cab

HEATER HOSES Silicone

AIR CONDITIONER with Integral Heater and Defroster

GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

Includes

- GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for
- GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure
- WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

VIRTUAL GAUGE, AIR APPLICATION Requires Premium Cluster

VIRTUAL GA,OIL TEMP,REAR AXLE Requires Premium Cluster

SEAT, DRIVER Air Suspension, High Back, Leather, 2 Arm Rests, Isolator, 7.5 Adjuster, 3 Chamber Lumbar, 6 Way Front Adjust, 3 Way Rear Cushion Adjust, 3-14 Degree Back Angle Adjustment, Adj Side Bolster, Bellows, Back Cyclor

GRAB HANDLE, EXTERIOR Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left Side at B-Pillar

MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Black, Heated, 7.5" Sq.

SEAT, PASSENGER {National} Non-Suspension, High Back, Fixed Back, Integral Headrest, Vinyl

MIRRORS (2) C-Loop, Power Adjust, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width

CAB INTERIOR TRIM Day Cab

Includes

- CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger
- DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Reading Lights; Integral to Overhead Console, Center Mounted
- SUN VISOR (3) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side

WINDSHIELD Heated, Single Piece

HOSE CLAMPS, HEATER HOSE Belleville Washer Type

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

CAB REAR SUSPENSION Air Bag Type

INSTRUMENT PANEL Wing Panel

SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral Clearance/Marker Lights

ACCESS, CAB Aluminum, Self-Cleaning, Open and Serrated Design, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab, Extended Cab or Sleeper Cab

WHEELS, FRONT DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs, Non-Standard Offset, with .5" Thick Disc

WHEELS, REAR DUAL DISC: 22.5x9.00 Rims, Powder Coat Steel, 5- Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEEL GUARDS, FRONT for Metric Hub Piloted Wheels with Flanged Mounting Nuts Mounted Between Hub and Wheel

WHEEL GUARDS, REAR for Metric Hub Piloted Wheels with Flanged Mounting Nuts, Mounted Between Hub & Wheel and Between Dual Wheels

BDY INTG, REMOTE POWER MODULE Mounted Inside Cab Behind Driver Seat, Up to 6 Outputs & 6 Inputs, Max 20 amp per Channel, Max 80-amp Total; Includes 1 Switch Pack with Latched Switches

(4) TIRE, REAR 12R22.5 Load Range H Drive

(2) TIRE, FRONT 315/80R22.5 Load Range L All-Position

Services Section:

WARRANTY 7-year bumper to bumper.

Plow and Body Outfitting:

PLOW FRAME- power tilt w/ wing mount and twin chain lift

PLOW- 11' full trip, reversing, sliding color lift HD sabre blades w/ 4 blade savers, carbide frame shoes, 18" rubber deflector, plow whips on the ends.

WING- 10' HD full trip hydraulic arms (cushion spring lower), carbide and cover blades, moldboard shoes (3).

HYDRAULICS- Transmission mounted, tandem gear, stainless steel oil lines and fittings as well as reservoir, 8 section valve, three stick electronic actuated controls, electronic spreader control.

SIDE DUMP- 10' side dump w/ remote lube, ¼" AR450 floor/tipper w/ I beam and cross members, AR450 front wall/safety wall, ½ cab shield, dual action hoist, side ladder, inner body step, shovel holder, color camera w/ screen (back up and in bed view), electric asphalt tarp, 30T pintle hook, electric plug, and glad hands, poly fenders and rear mud flaps. Zinc/epoxy primed baked paint.

LIGHTS- LED heated cab (4) and corner strobes, LED heated stop/tail/turn/and reverse lights. LED marker lights. LED heated spot and plow lights.

This truck shall be completed by October 1, 2024. A waiver of the completion date may be granted if the vendor is able to demonstrate a delay in the availability of equipment needed to meet the project specifications. The Town may or may not have a trade in truck with similar specifications. The Town will work out the details of a potential trade with the vendor at the time of delivery.

Bid Review and Selection Criteria:

The Town of Enfield will select the "lowest and responsible bidder." This does not mean that the vendor submitting the lowest priced proposal will automatically be awarded the bid. In addition to the purchase price, the Town of Enfield will consider criteria such as quality of the commodity, service reputation, suitability of the product for meeting the performance needs of the Town, and other factors that are relevant and appropriate in connection with the vehicle or material being procured.

Proposals will be accepted that deviate from the Scope of Work, but all such submissions must specifically state exceptions to the Scope of Work on their own page labeled "Exceptions."

Guidelines:

All Proposals become the property of the TOWN and will therefore be considered a public document which will be open to public viewing, after the bid opening. This proposal, if accepted, will become a legally binding addendum to the eventual contractual agreement with the TOWN. This request for proposal in no way commits the TOWN to make an award or reimburse any CONTRACTOR for any expense incurred in responding to this request.

Evaluation Criteria:

All proposals received in response to this RFP will be evaluated to determine if they are complete and meet the requirements specified in this RFP. The vendor will be chosen based on who will provide the “best value” taking into consideration the most beneficial combination of qualifications, services, costs, and who has met the requirements of this RFP. Only proposals judged to be responsive to the submission requirements set forth in this RFP will be evaluated.

The TOWN reserves the right:

- to accept or reject any or all bids in whole or in part and to accept other than the lowest price proposal;
- to waive any technical defect, qualification, omission, informality, or irregularity in any proposal received;
- to amend, modify, or withdraw this Request for Proposal;
- to require supplemental statements or information from a CONTRACTOR;
- to extend the deadline for responses to this Request for Proposal;
- to waive or correct any irregularities in proposals received;

The TOWN may award a contract based upon the proposals received without discussion of such proposals with proposers. Each proposal should therefore be submitted with the most favorable terms the proposer can make to the TOWN.

The Request for Proposal documents and Notice of Award shall be the agreement between the TOWN and successful proposer with respect to the matters dealt with herein, and such shall supersede all other oral and written proposals, representations, understandings, and agreements previously made or existing with respect to any such matter.

Qualification of Bidders:

Staff will review, analyze and evaluate all proposals and score them in accordance with the criteria described below. If needed, additional information may be requested from one or more CONTRACTORS.

Award will not be made solely on the basis of the cost of services. Evaluation factors to be considered in addition to cost shall be:

- The CONTRACTOR’s reputation based on past work experience with the TOWN and other references.
- Quality of workmanship or service provided.
- Adequate financial resources or the ability to obtain such resources as required to complete the performance of the project.
- Adequate experience, organization, technical and professional qualifications, personnel, skill, equipment, and ability.
- The ability to comply with the time frames proposal.

Each CONTRACTOR must be prepared to present satisfactory proof of their capacity and ability to successfully complete the requirements of this solicitation.

Proposals shall include a brief summary of similar projects or services provided (at least 3), including:

- The date (s) of project or service provided.
- The point of contact with name and telephone number of such clients.

The TOWN reserves the right to make whatever investigations or inquiries necessary to determine the competency and ability of any CONTRACTOR to complete the requirements of this solicitation. A review may include, but not be limited to, inspection of the CONTRACTOR's facilities and equipment, references, or previous contract performance.

Revisions:

Any questions or inquiries must be submitted in writing and received by 12:00 P.M. on Friday, April 7, 2023, no later than 7 calendar days prior to the proposal due date. Answers to all questions or information given to a CONTRACTOR in response to a formal request of a substantive nature will be posted on the TOWN's RFP page on the Town of Enfield, NH website (<https://www.enfield.nh.us/new-enfield-projects/pages/requests-proposals-rfps-qualifications-rfq>) no later than five (5) days prior to the due date.

Only such amendments, when issued by the TOWN, will be considered as being binding on the TOWN. Verbal explanations or instructions given by a TOWN employee to a CONTRACTOR in regard to this solicitation shall not be binding on the TOWN and shall be considered informal unless confirmed in writing by the TOWN. CONTRACTORS should note that all clarifications and exceptions, including those relating to the terms and conditions of the contract, are to be resolved prior to the submission of a proposal.

Contract:

The final contract will involve, at a minimum, the terms and conditions set forth in this RFP including the general conditions and may include those reflected in the specific proposal submitted. The content shall be the exclusive source of the CONTRACTOR'S rights and remedies and shall supersede any and all prior writings, negotiations or agreements of any kind.

The TOWN is exempt of all taxes.

All CONTRACTORS must comply with all applicable Equal Employment Opportunity laws and regulations.

THE TOWN OF ENFIELD IS AN EQUAL OPPORTUNITY PROVIDER AND EMPLOYER

Proposal Form

Project Title: **Six Wheel Municipal Plow Truck**

Proposal from _____ (hereinafter called "CONTRACTOR") a corporation organized and existing under the laws of the State of _____, as a partnership or an individual doing business as _____.

To the: Town of Enfield (hereinafter called "TOWN").

Cost Breakdown:

Cab and Chassis: \$ _____

Plows and Body Outfitting: \$ _____

Total Cost: \$ _____

The CONTRACTOR agrees that this proposal shall be good and may not be withdrawn for a period of thirty (30) calendar days after the scheduled closing time for receiving proposals.

The CONTRACTOR understands that the TOWN reserves the right to reject any or all proposals and to waive any informality in the proposals.

Submitted by: _____ Title: _____

(Business Address)

(Phone #)

(Email Address)

(Authorized Representatives Signature)

Please list any exceptions to the Bid Specifications separately.

Please supply three (3) references including a name, contact information, type of job completed, and date of job completion.